

TCP-B2-2



TCP-B2-2

KEY FEATURES

- 1080p HD-TVI
- Main Output: HD-TVI
- 2nd Output: Analog
- 2.9mm Fixed Lens
- OSD Setup
- Day-Night w/ IR
- D-WDR
- UTC
- DC12V

CONSTRUCTION

- Outdoor / Metal Housing

APPLICABLE PRODUCTS

- HD-TE4 / 4-ch HD-TVI DVR
- HD-TE8 / 8-ch HD-TVI DVR
- HD-TE16 / 16-ch HD-TVI DVR

TECHNICAL SPECIFICATIONS

Imaging Sensor	1/3" CMOS
Resolution	1080p TVI
Min. Illumination	Color : 1.0 lux , BW : 0.5lux / Color DSS : 0.002 lux , BW DSS : 0.001 lux
S/N Ratio	More Than 50dB (AGC off)
BRIGHTNESS	1 ~ 20 steps
SHUTTER	AUTO / MANUAL / FLICKER
SENS-UP	OFF /x2 / x4 / x6 / x8 / x10 / x15 / x20 / x25 / x30
AGC	1 ~ 15
DEFOG	OFF / AUTO
BACKLIGHT	OFF / HLC / BLC
DAY&NIGHT	AUTO / COLOR / B/W / EXT
WHITE BAL.	AUTO / AUTOext / PRESET / MANUAL
3D DNR/2D DNR	MIDDLE / HIGH / OFF / LOW
SHARPNESS	OFF / 1 ~ 10
MIRROR	OFF / V-FLIP/MIRROR/ROTATE
D-WDR	OFF / 0-8
PRIVACY	OFF / ON
MOTION	OFF /ON
ALC	OUTDOOR / INDOOR
FRAME RATE	1080P@30FPS / 1080P@25FPS
CVBS	NTSC / PAL
COM.	2400 / 4800 / 9600 / 19200 / 38400
CAM ID	0~255
OPERATING TEMPERATURE	-10℃ ~ +50℃ (Humidity : 0%RH ~ 80%RH)
STORAGE TEMPERATURE	-20℃ ~ +60℃ (Humidity : 0%RH ~ 90%RH)
Lens	2.9mm Fixed Board Lens
Input Voltage	DC12V
IR LEDs	24
IR LEDs Distance	50ft

DIMENSIONS

Unit: Inches (mm)

