

## TCP-E2-21



TCP-E2-21

### KEY FEATURES

- 1080p HD-TVI
- Main Output: HD-TVI
- 2nd Output: Analog
- 2.8~12mm Vari-focal
- Lens OSD Setup
- Day-Night w/ IR
- D-WDR
- UTC
- DC12V

### CONSTRUCTION

- Outdoor / Metal Housing

### APPLICABLE PRODUCTS

- HD-TE4 / 4-ch HD-TVI DVR
- HD-TE8 / 8-ch HD-TVI DVR
- HD-TE16 / 16-ch HD-TVI DVR

### TECHNICAL SPECIFICATIONS

|                       |                                                                            |
|-----------------------|----------------------------------------------------------------------------|
| Imaging Sensor        | 1/3" CMOS                                                                  |
| Resolution            | 1080p TVI                                                                  |
| Min. illumination     | Color : 1.0 lux , BW : 0.5lux / Color DSS : 0.002 lux , BW DSS : 0.001 lux |
| S/N Ratio             | More Than 50dB (AGC off)                                                   |
| BRIGHTNESS            | 1 ~ 20 steps                                                               |
| SHUTTER               | AUTO / MANUAL / FLICKER                                                    |
| SENS-UP               | OFF /x2 / x4 / x6 / x8 / x10 / x15 / x20 / x25 / x30                       |
| AGC                   | 1 ~ 15                                                                     |
| DEFOG                 | OFF / AUTO                                                                 |
| BACKLIGHT             | OFF / HLC / BLC                                                            |
| DAY&NIGHT             | AUTO / COLOR / B/W / EXT                                                   |
| WHTIE BAL.            | AUTO / AUTOext / PRESET / MANUAL                                           |
| 3D DNR/2D DNR         | MIDDLE / HIGH / OFF / LOW                                                  |
| SHARPNESS             | OFF / 1 ~ 10                                                               |
| MIRROR                | OFF / V-FLIP/MIRROR/ROTATE                                                 |
| D-WDR                 | OFF / 0-8                                                                  |
| PRIVACY               | OFF / ON                                                                   |
| MOTION                | OFF /ON                                                                    |
| ALC                   | OUTDOOR / INDOOR                                                           |
| FRAME RATE            | 1080P@30FPS / 1080P@25FPS                                                  |
| CVBS                  | NTSC / PAL                                                                 |
| COM.                  | 2400 / 4800 / 9600 / 19200 / 38400                                         |
| CAM ID                | 0~255                                                                      |
| OPERATING TEMPERATURE | -10℃ ~ +50℃ (Humidity : 0%RH ~ 80%RH)                                      |
| STORAGE TEMPERATURE   | -20℃ ~ +60℃ (Humidity : 0%RH ~ 90%RH)                                      |
| Lens                  | 2.8-12mm Vari-focal Lens                                                   |
| Input Voltage         | DC12V                                                                      |
| IR LEDs               | 36                                                                         |
| IR LEDs Distance      | 100ft                                                                      |

### DIMENSIONS

Unit: Inches (mm)

