



PN-E8

KEY FEATURES

- Available in 8-ch
- Decoding: 4ch. D1 / 720p / 1080p / 3MP@30fps / 4MP@22fps / 5MP@18fps
- Resolution: 5MP/4MP/3MP/1080p/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
- Monitor outputs: HDMI / VGA / BNC
- Audio
- 2 USB ports

HD REMOTE VIEWING

- Free DDNS service
- Mobile App
- WebViewer
- CMS

TECHNICAL SPECIFICATIONS

Model	PN-E8
Video Outputs	8
Monitor Outputs	HDMI / VGA / BNC
Pentaplex	Live , Record , Playback , Backup and Remote Access
IP Camera Input	8 ch. (96Mbps)
Decoding Capability	8ch. 720p@30fps / 8ch. 1080p@30fps / 8ch. 4MP@22fps / 8ch. 5MP@18fps
Support Protocol	ONVIF 2.4
Video Compression	MPEG-4 / H.264
Capture	JPEG
IP Resolution	Main Stream up to 5632x4224 / Auxiliary stream 4CIF
Resolution	5MP/3MP/1080p/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream
Playback Display Modes	6ch. 1080p / 4ch. 3MP / 3ch. 4MP / 2ch. 5MP
Dual Stream	Support
Search Modes	Time / Calendar / Event
Max Playback	4ch
Audio input / output	1 / 1
2-way audio	1st. Channel reuse
Audio compression	G.711A
Alarm in / out	N/A
Serial interface	RS-485
USB2.0 ports	2 x USB 2.0
Special Function	Supports Dropbox and Google Drive
Internal HDD bays	1 / Supports up to 4TB
POE Function	8 ch. (IEEE 802.3af)
Power supply	DC48V / 1.875A (POE)
Power Consumption	7W (without HDD & POE)
Dimensions	215x235x45 (mm)
Operating Temperature	0°C~ + 55°C / 10% - 90% RH